

MICOM-2EF *Front Mount*

**HF-SSB ALE Front Mount Digital Signal
Processing Radio**
125 watt PEP/Average 1.6-30 MHz



Features

- Enhanced features for better communications
- Ruggedized Mobile / Fixed Transceiver
- Front panel programming
- Advanced digital technology
- Conforms to MIL-STD 810 and EIA Specifications
- ALE per FED-STD-1045 and MIL-STD-188/141A
- High MTBF
- Complies with ISO 9001 Requirements
- Security access code
- Variable Bandwidth for optimal signal processing
- Voice activated digital squelch
- Programmable channel scan
- Digital noise blanking and clarifier
- Guard and Priority Channels
- Continuous duty operation (optional)
- Multi-language Liquid Crystal Display
- BITE(Built-in Test)
- Meets FCC and EMC standards
- Selectable front-end Attenuator
- Enhanced Voice Quality
- Excellent frequency stability
- Selectable Power Output
- Small Size, Light Weight
- Variable notch filter
- Sub-octave pre-selector
- Adaptable internal configuration options

MICOM-2EF is an advanced Ruggedized Digital Signal Processing transceiver, intended for very wide area radio communications. It provides, Voice, Data, Fax and E-mail solutions with a high degree of sophistication, signal quality and reliability, while being very simple to operate.

MICOM-2EF with its compact size provides maximum ease of installation. The Automatic Link Establishment-ALE (per FED-STD 1045 and MIL-STD 188/141A) is a STANDARD FEATURE of every MICOM-2EF.



Communications

MICOM-2EF *Front Mount*

MICOM-2EF Front Mount

HF-SSB ALE Trunk Mount Mobile Digital Signal Processing radio 125 watt PEP/Average 1.6-30 MHz

GENERAL					
Model Number:	M80AMN0KV5-K				
Frequency Range:	1.6 MHz Tx, 100 kHz-30 MHz Rx				
Number of Channels:	200: User programmable; Simplex or Half Duplex				
Scanning:	5 groups with up to 100 channels per group				
Frequency Stability:	0.6 PPM, (0.1 PPM optional)				
Frequency Drift (Aging):	1 PPM per year				
Synthesizer Lock Time:	10 msec max.				
Frequency Resolution:	10 Hz				
Audio Bandwidths @ -6dB:	Voice: 350 to 2700 Hz CW: 650 to 1150 Hz Low speed data: 1450 to 1950 Hz High speed data*: 350 to 3300 Hz				
Operating Temp. Range:	-30° to +60°C				
Humidity:	95% @ 50°C				
Operating Voltage:	13.8V DC ± 20% Neg. Ground				
ALE: Per FED-STD 1045 and MIL-STD 188/141A					
Current Drain @ 13.8 VDC	Receive Squelched		Transmit		
	Full Audio		Voice	2 Tone	1 Tone
	2.2A	3A	14A	23A	28A
Dimensions and Weights	Height mm/inch	Width mm/inch	Depth mm/inch	Weight Kg Lb	
	92 / 3.7	302 /11.9	270 /10.7	5.7	12.5

*Optional, for authorized users only.

TRANSMITTER	
Output Power:	125W P.E.P. and average
Reduced Power Levels:	25W, 62W, 100W (RSS Programmable)
Audio Bandwidth Ripple:	3 dB
Intermodulation:	-31 dB/P.E.P. (-35 dB/P.E.P. Typical. Note 1)
Harmonic Emissions:	-64 dB/P.E.P. (-70 dB/P.E.P. Typical. Note 1)
Spurious Emissions:	-64 dB/P.E.P. (-70 dB/P.E.P. Typical. Note 1)
Carrier Suppression:	-50 dB/P.E.P.
Undesired Sideband Suppression:	-55 dB/P.E.P.
Audio Distortion:	2.5%
1/2 Power Mic. Sensitivity:	25 to 125 mV (RMS)/600 ohms
Hum & Ripple:	-50 dB
Inband Noise:	-60 dB (30 Hz BW)
Tx/Rx Switching Time:	10 msec
Tx Tuning Adjustments:	None

Note 1: Values noted as typical are valid over 90% or more of the frequency range.

RECEIVER	
Sensitivity (SINAD) SSB:	0.5 μ v for 10 dB SINAD (0.3 μ v Typical. Note 1) 0.1-1.6 MHz – reduced performance
1/2 Rated Power Sensitivity:	1 μ v for 2.5W audio @ speaker
Selectivity:	-6 dB @ 350 to 2700 Hz -60 dB @ -1 kHz, +4 kHz
Image Rejection:	-80 dB
IF Rejection:	-85 dB
Undesired Sideband Rejection:	-55 dB @ -1 kHz
Spurious Rejection:	-80 dB
Intermodulation Rejection:	-80 dB
Cross Modulation Rejection:	-100 dB @ 100 kHz
Desensitization:	-100 dB @ 100 kHz
Reciprocal Mixing:	-100 dB @ 100 kHz
Audio Power @ Speaker:	5W @ 2.5% distortion
RGC Range:	5 μ v 1V (2 dB change in output level)
RGC Time Constants Voice:	Attack time 10 msec Release time 1500 msec
Data:	Attack time 10 msec Release time 10 msec
Squelch:	Constant SINAD (digital)
Clarifier Range:	± 200 Hz in 10 Hz steps
Receiver Tuning Adjustments:	None
Preselector Sections:	Sub-octave (1.6 MHz to 30 MHz range)
Antenna Input Protection:	20 kV maximum transient, 100V RMS for 2 minutes

MILITARY & INDUSTRIAL STANDARDS

MICOM-2EF meets the following US military and industrial standard requirements for adverse environmental conditions (without the need of external shock mounts)

Environmental Condition	US Military STD 810C	US Military STD 810D	US Military STD 810E
Vibration	Method 514.2	Method 514.3	Method 514.4
Shock	516.2	516.3	516.4
Rain	506.1	506.2	506.3
Dust	510.1	510.2	510.3
Salt Fog	509.1	509.2	509.3

The MICOM-2EF also meets the EIA-RS152B for shock, vibration and applicable test procedures, US FCC for channel occupancy, spurious, interference and frequency tolerance. It is manufactured according to the demanding standards of ISO 9000 and EMC (Electromagnetic Compatibility).

FCC Information: Emissions: J3E, R3E, H3E, J2A, J2B, B8C
FCC Applicable Parts of Rules: 15, 80, 90
FCC Type Acceptance Number: ABZ9QCC1635
With High Stability Option: ABZ9QCC1634

OPTIONS

- RS232 Remote Control Interface
- Linear Amplifier Interface
- Phone Patch Interface
- Data/Fax Modem interface
- Interlink Interface
- 24 VDC Operation
- RSS for PC (Radio and ALE)
- High (0.1 PPM) Frequency stability

MAJOR ACCESSORIES

- Phone Patch
- Interlink (FM-HF repeater)
- Automatic Antenna Tuner
- Continuous Duty Kit
- AC Power Supply
- Automatic Telephone Interconnect
- 1 kW Amplifier
- 400 W Amplifier
- Antennas and Grounding kit
- Data/Fax Modem
- CW Key & Headphones

Specifications subject to change without notice.



MOBAT Communications Ltd.
3 Israeli Shimon St. P.O. 5090
Ind. zone rishon le Zion 75151 Israel
Tel: 972 3 9518050 ext. 205
Fax: 972 3 9527233
E-mail: govors@mobat.com
web: www.mobat.com

MOBAT USA
1720 west Paul dirr dr.
Tallahassee fl. 32310
Tel: 850 580 0444
Fax: 850 580 2626
E-mail: marketing@mobatusa.com
web site: www.mobat.com

Distributor